



Table lamp for indirect and diffused lighting. The 4 W LED source is housed in the base. The light intensity is adjustable through a touch dimmer on the base. Aluminium structure and transparent glass diffuser.

FINISHINGS

Anodised Black
 3000K - cod. 14101X000
 2700K - cod. 14101XOK27

Anodised Brass
 3000K - cod. 14150X000
 2700K - cod. 14150XOK27

ALL RAL COATING AND GALVANIC FINISHES AVAILABLE UPON REQUEST

LIGHT EMISSION

Light source power: 4,2W	Efficacy 3000K: 12lm/W
Power absorption: 6W	Source Flux 2700K: 374lm@350mA
Light Emission: Diffuse	Emitted Flux 2700K: 70lm
Light Direction: Indirect Downlight	Efficacy 2700K: 12lm/W
Light Source: Discrete LED	CCT: 2700/3000K
Source Flux 3000K: 391lm@350mA	CRI: 90
Emitted Flux 3000K: 73lm	Lifetime: >55000h

ELECTRICAL FACTS

Stand-by absorption: <0.5
 Mains Voltage: 100/240VAC
 Master output: 24VDC; max 0.63A
 Ta max: 40°C

PACKAGING DATA

Box dimensions: 21x21x27 cm
 Volume: 0,012 m³
 Gross weight: 1,7 kg

