


Flo Floor



Foster+Partners, 2011



Floor lamp in varnish coated aluminium and steel for diffused directional light. The head rotates 300° to direct the 3W-LED light and the structure swivells 120° on the base. 2-step push switch positioned on the head.

FINISHINGS

 Black Soft Touch 3000K - cod. 94501ST00 2700K - cod. 94501STK27	 Brushed Nickel 3000K - cod. 94544000 2700K - cod. 94544K27
 Matt White 3000K - cod. 945020P00 2700K - cod. 945020PK27	 Metallic Bronze 3000K - cod. 94529MT00 2700K - cod. 94529MTK27
 Matt Red 3000K - cod. 945030P00 2700K - cod. 945030PK27	 Gun Metal 3000K - cod. 94532000 2700K - cod. 94532K27
 Matt Yellow 3000K - cod. 945050P00 2700K - cod. 945050PK27	 Gold Brushed 3000K - cod. 94545SL00 2700K - cod. 94545SLK27

ALL RAL COATING AND GALVANIC FINISHES AVAILABLE UPON REQUEST

LIGHT EMISSION

Light source power: 5,06W
Power absorption: 7,5W
Light Emission: Diffuse
Light Direction: Directional
Light Source: Discrete LED
Source Flux 3000K: 395lm@550mA
Emitted Flux 3000K: 314 lm

Efficacy 3000K: 42lm/W
Source Flux 2700K: 380lm@550mA
Emitted Flux 2700K: 302lm
Efficacy 2700K: 40 lm/W
CCT: 2700/3000K
CRI: 90
Lifetime: >55000h

ELECTRICAL FACTS

Stand-by absorption: <0.5
Mains Voltage: 100/240VAC
Master output: 24VDC; max 0.83A
Ta max: 40°C

PACKAGING DATA

Box dimensions: 123x56x8 cm
Volume: 0,053 m³
Gross weight: 4,8 kg

